



Parscan New 48V – Systematic diversity

The compact 48V spotlight system for galleries and boutique offices

The evolution of Parscan brings a broad technical platform for even more quality of light, design flexibility and digital connectivity. A new generation of Spherolit lenses projects the light onto the target plane – precisely, uniformly and with superior efficiency. Miniaturised 48V technology reduces the dimensions of luminaires, track and adapters and enables maximum optical performance even from size XS. The support bracket integrates flush into the overall

cylindrical shape: a timeless, minimalist design for projects such as galleries, boutique offices and the illumination of display cases. Parscan spotlights can be customised to suit the specific installation situation thanks to tool-free interchangeable lens units, a wide range of accessories and add-on control units.

Parscan New 48V for Minirail track



Structure and characteristics

The features described here are typical of products in this range. Special versions may offer additional or varying features. A comprehensive description of the features of individual products can be found on our website.

1 ERCO lenses

- Made of optical polymer
- Spherolit lenses: narrow spot, spot, flood, wide flood, extra wide flood, oval flood or wallwash
- Zoom lenses: zoom spot; continuously focusable
- Projection lenses: narrow framing or wide framing; continuously focusable

2 Lens unit

- Rotatable through 360°
- Polymer, white or black
- Contour spotlights with framing attachment

3 ERCO LED-module

- High-power LEDs: warm white (2700K or 3000K), neutral white (3500K or 4000K), tunable white (2700-7500K) or RGBW
- Collimating lens made of optical polymer

4 Housing and bracket

- White (RAL9002) or black
- Die cast zinc or cast aluminium, powder-coated
- Pivotal 0°–90°
- Bracket: cast aluminium/polymer; rotatable through 360° on adapter

5 Control gear

- On-board Dim or Casambi Bluetooth
- On-board Dim version: rotary control for control of brightness on the luminaire

6 ERCO Minirail adapter

Variants on request

- Housing: 10,000 further colours
- Please contact your ERCO consultant.



Design and application:
www.erco.com/parscan-48V

Parscan New 48V for Minirail track



Zoom spotlights

The light beam diameter can be infinitely adjusted from spot (15°) to wide flood (65°) by simply turning the lens. Zoom spotlights are particularly suitable for illuminating areas with changing exhibits and merchandise.



Contour spotlights

Framing attachments enable a sharply defined light beam. In this way fascinating effects can be created with contour spotlights, where crisply illuminated pictures appear to illuminate from within.



Tunable white technology

Just as the colour temperature outdoors changes continuously during the day, the colour temperature of the lighting can be adjusted indoors to e.g. support lighting concepts for Human Centric Lighting.



RGBW luminaires

Using coloured light, the environment can be designed and transformed with either subtle or dramatic contrasts. LEDs enable you to generate coloured light very efficiently and flexibly.

Special characteristics


	Zoom spotlight
	Contour spotlight
	Tunable white
	Coloured light

	ERCO high-power LEDs		Excellent thermal management		On-board Dim
	Efficient Spherolit technology		EMC-optimised		Casambi Bluetooth
	Different light distributions		Various housing colours		
	Oval flood, freely rotatable		Various construction sizes		
	Different light colours		Pivotable through 90°		
			Accessory for maximum visual comfort		

Parscan New 48V for Minirail track – Luminaire arrangement

Spotlights

Narrow spot, Spot, Flood




Works of art, merchandise and architectural details are effectively accentuated with Parscan. The ideal angle of tilt (α) for this is around 30°. The object is modelled without distorting the effect as a result of excessive shadowing. It also prevents shadows cast by the observer.

Arrangement: $\alpha = 30^\circ$

Zoom spotlights

Zoom spot




Zoom spotlights feature a continuously adjustable beam angle. With the spot to wide flood zoom range, smaller works of art can be accentuated effectively at an inclination angle (α) of approximately 30°. The object is modelled without distorting the effect as a result of excessive shadowing. It also prevents shadows cast by the observer.


Arrangement: $\alpha = 30^\circ$

Contour spotlights

Narrow framing, Wide framing




Contour spotlights generate freely adjustable, crisp-edged light beams. As a result fascinating effects can be created where pictures appear to illuminate from within. Select narrow framing to accurately illuminate small exhibits from a long distance and wide framing to accurately illuminate large exhibits from a short distance.



Floodlights

Wide flood, Extra wide flood, Oval flood




The ideal angle of tilt (α) for flood-lighting objects with an elongated, rectangular shape, e.g. pictures, sculptures or merchandise displays, is approximately 30°.

Arrangement: $\alpha = 30^\circ$


Parscan New 48V for Minirail track – Luminaire arrangement

Lens wallwashers Wallwash



For uniform vertical illuminance, the distance (a) of Parscan lens wallwashers from the wall should be around one third of the room height (h). This results in an angle of tilt (α) of approx. 35°.

Arrangement: $a = 1/3 \times h$ or
 $\alpha = 35^\circ$




For good longitudinal uniformity, the luminaire spacing (d) of Parscan wallwashers may be up to 1.5 times the distance to the wall (a).

Arrangement: $d \leq 1.5 \times a$

Optimal wall distances and luminaire spacing values for individual products are specified in the wall-washer tables at www.erco.com.

Parscan 48V for Minirail track

Size



XS
Ø 32mm

LED module

Maximum value at 4000K CRI 92

3.1W/404lm	3.1W/404lm (Narrow spot)
------------	--------------------------

Light colour

	2700K CRI 92		3500K CRI 92
	3000K CRI 92		4000K CRI 92
	3000K CRI 97		

Light distribution


Spotlights	Floodlights
 Narrow spot	 Wide flood
 Spot	 Extra wide flood
 Flood	 Oval flood
Zoom spotlights	Lens wallwashers
 Zoom spot	 Wallwash

Control

	On-board Dim
	Casambi Bluetooth + DALI via Gateway

Colour (housing)

	White		10,000 colours *
	Black		



S
Ø 60mm

LED module

Maximum value at 4000K CRI 92

8.1W/1149lm	3.1W/339lm (Narrow spot)
-------------	--------------------------

Light colour

	2700K CRI 92		3500K CRI 92
	3000K CRI 92		4000K CRI 92
	3000K CRI 97		

Light distribution

Spotlights	Floodlights
 Narrow spot	 Wide flood
 Spot	 Extra wide flood
 Flood	 Oval flood
Zoom spotlights	Lens wallwashers
 Zoom spot	 Wallwash
Contour spotlights	
 Narrow framing	
 Wide framing	



Control

	On-board Dim
	Casambi Bluetooth + DALI via Gateway

Colour (housing)

	White		10,000 colours *
	Black		

	Lenses		Lens Units		Snoot		Add-on Control Units
	Filter		Honeycomb louvre		Barn doors		DALI-Casambi Gateway




* available on request

www.ercoscan.com/parscan-48V



Parscan 48V for Minirail track

Size



M
Ø 92mm

LED module

Maximum value at 4000K CRI 92

18.2W/2585lm

4,2W/426lm (Narrow spot)

12.6W/1338lm

Light colour

2700K CRI 92

3500K CRI 92

3000K CRI 92

4000K CRI 92

3000K CRI 97

Tunable white

Light distribution

Spotlights

Narrow spot

Spot

Flood

Zoom spotlights

Zoom spot

Contour spotlights

Narrow framing

Wide framing

Floodlights

Wide flood

Extra wide flood

Oval flood

Lens wallwashers

Wallwash

Spotlights

Spot

Flood

Zoom spotlights

Zoom spot

Contour spotlights

Narrow framing

Wide framing

Floodlights

Wide flood

Extra wide flood

Oval flood

Lens wallwashers

Wallwash

Control

On-board Dim

Casambi Bluetooth + DALI via Gateway

Casambi Bluetooth + DALI via Gateway

Colour (housing)

White

Black

10,000 colours *


White

Black

10,000 colours *

Accessory		Lenses		Lens Units		Snoot		Add-on Control Units
		Filter		Honeycomb louvre		Barn doors		DALI-Casambi Gateway

8



* available on request

www.erco.com/parscan-48V

